

Northumbria Research Link

Citation: Giannakis, Iraklis, Warren, Craig, Giannopoulos, Antonios and Sofroniou, Anastasia (2021) Fractal-Based Orthonormal Basis for Compressing and Reducing the Dimensionality of Full-Waveform Inversion for Hydrogeological Applications Using Ground-Penetrating Radar. In: EGU General Assembly 2021: Gather Online, 19th April - 30th April 2021.

URL: <https://doi.org/10.5194/egusphere-egu21-16464> <<https://doi.org/10.5194/egusphere-egu21-16464>>

This version was downloaded from Northumbria Research Link:
<http://nrl.northumbria.ac.uk/id/eprint/46729/>

Northumbria University has developed Northumbria Research Link (NRL) to enable users to access the University's research output. Copyright © and moral rights for items on NRL are retained by the individual author(s) and/or other copyright owners. Single copies of full items can be reproduced, displayed or performed, and given to third parties in any format or medium for personal research or study, educational, or not-for-profit purposes without prior permission or charge, provided the authors, title and full bibliographic details are given, as well as a hyperlink and/or URL to the original metadata page. The content must not be changed in any way. Full items must not be sold commercially in any format or medium without formal permission of the copyright holder. The full policy is available online: <http://nrl.northumbria.ac.uk/policies.html>

This document may differ from the final, published version of the research and has been made available online in accordance with publisher policies. To read and/or cite from the published version of the research, please visit the publisher's website (a subscription may be required.)



UniversityLibrary



Fractal-Based Orthonormal Basis for Compressing and Reducing the Dimensionality of Full-Waveform Inversion for Hydrogeological Applications Using Ground-Penetrating Radar

Iraklis Giannakis¹, Craig Warren², Antonios Giannopoulos³, and Anastasia Sofroniou⁴

¹School of Geosciences, University of Aberdeen, Meston Building, Kings College, Aberdeen, UK, AB24 3FX

²Department of Mechanical and Construction Engineering, Northumbria University, Newcastle, UK, NE1 8ST

³School of Engineering, The University of Edinburgh, Edinburgh, EH9 3FG, UK

⁴School of Computing and Engineering, University of West London, London, W5 5RF, UK

Full-waveform inversion (FWI) using ground-penetrating radar (GPR) is gaining momentum as a powerful hydrogeological tool for inferring the hydraulic properties of soils between boreholes [1]. Nonetheless, the large computational requirements of FWI make it often unattainable with limited practical uptake [2]. In addition, the inability to accurately reconstruct the loss mechanisms and the need for a good initial model, further reduce the applicability of FWI [1], [2].

In order to overcome the aforementioned limitations, we suggest a novel framework that substantially reduces the optimization space of FWI which consequently reduces the overall computational requirements [2]. This methodology assumes that the water fraction of the investigated medium follows a fractal distribution [3]. Based on that, using a principal components analysis on 3000 randomly generated fractals, we build an orthonormal basis that is fine-tuned for fractal correlated noise. Furthermore, it is proven [2], that fractal correlated noise is highly compressible and can be sufficiently represented with just 30-40 principal components. This reduces the optimization space since now FWI needs to fine-tune just these 30-40 parameters instead of every cell of the investigated medium [2].

The involved fractals describe the distribution of the water fraction that is subsequently transformed to dielectric properties via a semi-empirical formula that relates readily available soil properties to the frequency dependent complex electric permittivity [4], [5]. Via this approach, we overcome the need for a simultaneous FWI for both permittivity and conductivity [6]. This further reduces the optimization space and overcomes pitfalls associated with reconstructing loss mechanisms [2].

References

[1] Klotzsche, A., Vereecken, H., & Kruk van der J., (2019), Review of Crosshole Ground-Penetrating Radar Full-Waveform Inversion of Experimental Data: Recent Developments, challenges, and Pitfalls, *Geophysics*, vol. 84, pp. H13-H28.

- [2] Giannakis, I, Giannopoulos, A., Warren, C. & Sofroniou, A., (2021), Fractal-Constrained Crosshole/Borehole-to-Surface Full Waveform Inversion for Hydrogeological Applications Using Ground-Penetrating Radar, IEEE Transactions on Geoscience and Remote Sensing, Early Access.
- [3] Turcotte, L. (1992), Fractal and Chaos in Geology and Geophysics, Cambridge, UK: The Press Syndicate of the University of Cambridge.
- [4] Peplinski, N. R., Ulaby, F. T., & Dobson, M. C., (1995), Dielectric Properties of Soils in the 0.3-1.3 GHz Range, IEEE Transactions on Geoscience and Remote Sensing, vol. 33, no. 3, pp. 803-807.
- [5] Giannakis, I., Realistic Numerical Modelling of Ground Penetrating Radar for Landmine Detection, (2016), PhD Thesis Submitted at The University of Edinburgh.
- [6] Meles, G. A., Kruk, van der J., Grennhalgh, S. A., Ernst, J. R., Maurer, H & Green, A. G., (2010), A New Vector Waveform Inversion Algorithm for Simultaneous Updating of Conductivity and Permittivity Parameters from Combination Cross/Borehole-to-Surface GPR Data, IEEE Transactions on Geoscience and Remote Sensing, vol. 48, no. 9, pp. 3391-3407.